

Inner layer fluororubber, outer layer silicone steel wire hose

Product images	Application	Characteristic	Structure
 ► Hose wall: FDA certified food grade silicone ► Reinforcement layer: Four layer polyester fabric	► Transport of liquids	► Corrosion preventive	► Color: translucent
	► Extraction of air/steam	► Smooth inner wall	► Temperature: -40/+220 °C
	► CIP and SIP cleaning	► Odorless/Odorless	► Length can be customized
	► Food factory	► Good liquidity	
	► Medical equipment	► Good airtightness	
	► Cosmetics industry	► High temperature and steam resistance	
		► FDA certification	

Part Number	Internal diameter mm	Outer diameter mm	Wall thickness mm	Weight kg/m	Burst pressure bar	Coil length m
ZS04-019-6	19	30	5.5	0.630	≥25	6
ZS04-025-6	25	36	5.5	0.781	≥25	6
ZS04-032-6	32	43	5.5	0.958	≥19	6
ZS04-038-6	38	49	5.5	1.109	≥17	6
ZS04-051-6	51	62	5.5	1.436	≥14	6
ZS04-063-6	63	74	5.5	1.739	≥11	6
ZS04-076-6	76	87	5.5	2.066	≥9	6
ZS04-089-6	89	100	5.5	2.371	≥8	6
ZS04-102-6	102	113	5.5	2.722	≥6	6

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.